

Ljudtester										
Produkt	Glas		Vikt	RISE			Intygs nr.	Typ	Anm.	Trö. FD
				Accrediterat lab						
	Ytterbåge	Innerbåge	kg/m ²	Rw	Tåg C	Bil Ctr	RISE	nr.		
SF-2010 Vrid	T4-16		30	34	33	29	PX14150-A5	Std.		
SF-2010 Vrid	4-14-4-15-6,8		35,8	38	36	31	9P08415-C1			
SF-2010 Vrid	6-15-4-15-4		35	38	36	32	PX14150-A3	20		
SF-2010 Vrid	8-12-4-16-4		40	38	36	32	9P08415-B1	21		
SF-2010 Vrid	6-12-4-12-8,8LP		46	41	39	35	9P08415-D1	22		
SF-2010 Vrid	8,8LP-10-4-12-8,8LP		52	43	41	38	5P03577-B3	24		
SF-2010 Vrid	6-12-4-10-11PD		51,6	38	37	33	9P08415-F1		Brand	
SF-2010 Fast	T4-16		30	33	31	27	9P08415-A5			
SF-2010 Fast	4-14-4-15-6,8*		35,8	37	35	30	9P08415-A3		*motsv solskydd ut	
SF-2010 Fast	6-12-4-12-8,8LP		45,8	41	38	33	9P08415-A4	22		
SF-2010 Fast	8,8LP-10-4-12-8,8LP		52	44	42	38	5P03577-C1	24		
SF-2010 Fast	12,8LP-8-4-10-8,8LP		62	46	44	40	5P03577-C2			
SF-2010 Fast	12,8LP-22-8,8LP		52	46	44	39	9P08415-A1		Dubbelruta	
SF-2010 Fast	8,8LP-10-4-10-11PD		57,4	40	39	37	9P08415-E1		Brand	
INTAKT 2+1	4	4- 16 -4	30	39	37	31	4P00592-9	Std.		
INTAKT 2+1	6	4- 16 -4	35	41	39	35	4P00592-7	1		
INTAKT 2+1	6	4- 16 -6	40	42	39	35	4P04344-2	2		
INTAKT 2+1	6	4- 18 -8	45	44	41	36	4P04729-6	3		
INTAKT 2+1	6,8*	4- 18 -8	45,5	46	43	38	4P04729-7	4		
INTAKT 2+1	6,8*	8-16-8,8LP	57	46	45	41	3P03622-9	5		
INTAKT 2+1	6,8	4-16-8,8LP	47	47	44	39	4P04729-16	6		
INTAKT 2+1	6,8	4-16-12,8LP	57	48	46	43	4P04729-14	7		
INTAKT 2+1	6	4-16-11PD	51,6	43	41	37	9P08415-L1		Brand	
2+1 Mötesbåge	4	4- 16 -4	30	39	37	31	4P00592-14	Std.		
2+1 med VL	4	4- 16 -4	30	37	36	32	6P10385-A	Std.		
2+1 med VL	6,8*	4- 18 -8	45	41	39	36	6P10385-B	4		
INTAKT 3-glas	T4-16		30	34	32	27	4P04344-1	Std.		
INTAKT 3-glas	6-15-4-15-4		35	37	35	31	6P10385-D	20		
INTAKT 3-glas	6-12-4-12-8,8LP		46	41	39	35	6P10385-E	22		
INTAKT 3-glas	8,8LP-10-4-12-8,8LP		52	43	41	38	5P0377-A5	24		

När det gäller Intakt 2+1 glasning hamnar solskyddsglaslet som mitre glas dvs ingen påvekan på ljudreduktionen så den styrs av inre & yttre glas.