



### Main

Enclosure type	Distribution enclosure
Range of product	Pragma
Device short name	Pragma
Accessories included with enclosure	1 terminal block Blanking plate strip Identification label Marking kit

### Complementary

Enclosure mounting	Surface
[In] rated current	160 A
Number of horizontal rows	5
Number of 18 mm modules per row	24
Total number of 18 mm modules	120
Type of rail	DIN
Cable entry	Cable or tube Cut-out plates Removable plates Trunking
Comb busbar and distribution block compatibility	XE compatible
Number of terminal blocks	1 earth Quick 44
Distribution block outgoers	1 x 50 mm <sup>2</sup> earth 3 x 25 mm <sup>2</sup> earth 40 x 6 mm <sup>2</sup> earth
Power dissipation in W	94 W
Enclosure material	Metal front face Metal back part Technoplastic front face Technoplastic back part
Width	550 mm
Height	900 mm
Depth	148 mm
Colour	Metal grey front face Titanium white enclosure

### Environment

Standards	EN 60439-3 EN 60695-2-11 IEC 60439-3 IEC 60529 IEC 60695-2-11 IEC 60947-7-1 IEC 62262
Fire resistance	750 °C front face IEC 60695-2-1 750 °C back part IEC 60695-2-1
IP degree of protection	IP30 IEC 60529
IK degree of protection	IK08 IEC 62262
Electrical shock protection class	Class II

Ambient air temperature for operation	-25...60 °C
RoHS EUR conformity date	0810
RoHS EUR status	Compliant

### Garantie contractuala

Period	18 luni
--------	---------